

K 35/4 Mehanička ručna presa sa izmenjivim umetcima 6 - 150 mm²

**K4
SERIE**



- Zamena matrice za presovanje bez alata
- Optimizovano za kablovske uvodnice i konstrukciju kontrolnog ormara
- Energetski efikasan mehanički pogon koji se lako održava
- Usko presovanje
- Teleskopske drške - podesive
- Rotirajuća stezna glava za 360°
- Brza zamena matrice za presovanje bez podešavanja posebnim sistemom fiksiranja

Tehničke karakteristike

Dužina	420-590mm
Težina	1,9 kg
Kataloška oznaka	K354

Oprema koja se posebno poručuje

Metalni kofer SK65L

Izmenjive matrice za:

Cu cevaste kablovske papučice, std. tip od 6-150mm ²		
Izolovane kablovske papučice i spojnice, std. tip, izolovani pin konektori od 10-70mm ²		
Cevaste kablovske papučice i konektori, za fine licnaste provodnike od 10-35mm ²		
Cevaste kablovske papučice i konektori od nerđajućeg čelika (VA) - ubodno presovanje od 1.5-2.5 mm ²		
Cevaste kablovske papučice i konektori od nerđajućeg čelika (VA) - dvostruko ubodno presovanje od 4-16mm ²		
Cevaste kablovske papučice i konektori od nikla - ubodno presovanje od 1.5-2.5mm ²		
Cevaste kablovske papučice i konektori od nikla - dvostruko ubodno presovanje od 4-16mm ²		
Cu kablovske papučice (DIN 46235) i konektore (DIN 46267, part 1) prema DIN od 6-120 mm ²		
Bezlemni terminali (DIN 46234), konektori i pin terminali (DIN 46230) prema DIN od 10-35mm ²		
Izolovani bezlemni terminali i konektori od 10-16 mm ²		
Oblikovanje spojnica Cu i Al za sektorske kablove od 16 sm - 150 se / 120 sm mm ²		
Al kablovske papučice i konektori po DIN od 10 rm/sm, 95 re/se mm ²		
Bimetalne Al/Cu kablovske papučice i konektori (Al strana um. HA4, Cu strana um. HD4) od 10 rm/sm, 95 re/se mm ²		
C kleme od 10-35 mm ²		
Hilzne od 10-50 mm ²		

Za više detalja o izmenjivim matricama pogledajte odeljak : [IZMENJIVE MATRICE](#)