

PK 120 U Hidraulična glava sa izmenljivim umetcima 10 - 400 mm²





































**K13
SERIE**



- Veliki opseg presovanja do 400mm²
- H stezna glava rotirajuća za 360° kada nije pod pritiskom
- Za povezivanje na hidraulične pumpe sa radnim pritiskom od 700bar

Odgovarajuće za:
- Izmenjive matrice serije 13, široko presovanje

Tehničke karakteristike	
Sila presovanja	120kN
Hod klipa	20mm
Opseg presovanja	10-400mm ²
Radni pritisak	max. 700bar
Dužina	320mm
Težina	3.7kg
Kataloška oznaka	PK120U
Isporuka obuhvata	kat. oznaka
Torba za nošenje	TT2
Oprema koja se posebno poručuje	
Izmenjive matrice za:	
Cu cevaste kablovske papučice i konektori, std. tip od 16-400mm ²	 
Izolovane kablovske papučice konektori, izolovani pin konektori od 10-150mm ²	 
Cevaste kablovske papučice i konektori, za fine licnaste provodnike od 10-150mm ²	 
Cevaste kablovske papučice i konektori od nerđajućeg čelika (VA) - dvostruko ubodno presovanje od 16-50mm ²	 
Cevaste kablovske papučice i konektori od nerđajućeg čelika (VA) - jednostruko ubodno presovanje od 70-95mm ²	 
Cevaste kablovske papučice i konektori od nikla - dvostruko ubodno presovanje od 16-50mm ²	 
Cevaste kablovske papučice i konektori od nikla - jednostruko ubodno presovanje od 70-95mm ²	 
Cu kablovske papučice (DIN 46235) i konektore (DIN 46267, part 1) prema DIN od 10-300 mm ²	 
Duple kompresione Cu kablovske papučice 2x50 - 2x120mm ²	 
Bezlemni terminali (DIN 46234), konektori i pin terminali (DIN 46230) prema DIN od 16-150mm ²	 
Izolovani bezlemni terminali i konektori od 10-95 mm ²	 
Oblikovanje spojnica Cu i Al za sektorske kablove od 10 sm - 300 se / 300 sm mm ²	 
Al kablovske papučice i konektori po DIN od 10 sm - 300 re / 300se mm ²	 
Bim. Al/Cu kablovske papučice i konektori od 10sm - 300re / 300se mm ²	 
C kleme od 10-70 mm ²	 
H kleme 70-120mm ²	 
Hilzne od 25-240 mm ²	 

Za više detalja o izmenjivim matricama pogledajte odeljak : [IZMENJIVE MATRICE](#)