

PK 25/2 Hidraulična glava sa izmenljivim umetcima 16 - 625 mm²



**K13
SERIE**

**K25
SERIE**



- Za izmenljive matrice prema DIN 48083 deo 3
 - Veoma veliki opseg presovanja do 625mm²
 - Stezna glava sa brzokidajućom spojkom, rotirajuća za 360° kada nije pod pritiskom
 - Za povezivanje na hidraulične pumpe sa radnim pritiskom od 700bar
- Odgovarajuće za:
- Izmenljive matrice serije 25, široko presovanje
 - Uz adapter 25A13 takodje je moguće koristiti izmenljive matrice serije 13, široko presovanje

Tehničke karakteristike

Sila presovanja	250kN
Hod klipa	20mm
Opseg presovanja	16-625mm ²
Radni pritisak	max. 700bar
Dužina	335mm
Težina	5.3kg
Kataloška oznaka	PK252
Isporuka obuhvata	kat. oznaka
Torba za nošenje	TT2

Oprema koja se posebno poručuje

Adapter za presovanje serije 13

25A13

Izmenljive matrice serije 25

Cu cevaste kablovske papučice i konektori, std. tip	300-400mm ²		
Cevaste kablovske papučice i konektori, za fine licnaste provodnike	240mm ²		
Cu kablovske papučice (DIN 46235) i konektore (DIN 46267, part 1)	300-625mm ²		
Oblikovanje spojnica Cu i Al za sektorske kablove	400-500mm ²		
Al kablovske papučice i konektori po DIN	400-500mm ²		
Bim. Al/Cu kablovske papučice i konektori	400-500mm ²		
C kleme	35-185mm ²		

Izmenljive matrice serije 13:

Cu cevaste kablovske papučice i konektori, std. tip od 16-400mm ²		
Izolovane kablovske papučice konektori, izolovani pin konektori od 10-150mm ²		
Cevaste kablovske papučice i konektori, za fine licnaste provodnike od 10-150mm ²		
Cevaste kablovske papučice i konektori od nerdajućeg čelika (VA) od 16-50mm ²		
Cevaste kablovske papučice i konektori od nerdajućeg čelika (VA) od 70-95mm ²		
Cevaste kablovske papučice i konektori od nikla - dvostruko ubodno presovanje od 16-50mm ²		
Cevaste kablovske papučice i konektori od nikla - jednostruko ubodno presovanje od 70-95mm ²		
Cu kablovske papučice (DIN 46235) i konektore (DIN 46267, part 1) prema DIN od 10-300 mm ²		
Duple kompresione Cu kablovske papučice 2x50 - 2x120mm ²		
Bezlejni terminali (DIN 46234), konektori i pin terminali (DIN 46230) prema DIN od 16-150mm ²		
Izolovani bezlejni terminali i konektori od 10-95 mm ²		
Oblikovanje spojnica Cu i Al za sektorske kablove od 10 sm - 300 se / 300 sm mm ²		
Al kablovske papučice i konektori po DIN od 10 sm - 300 re / 300se mm ²		
Bim. Al/Cu kablovske papučice i konektori od 10sm - 300re / 300se mm ²		
C kleme od 10-70 mm ²		
H kleme 70-120mm ²		
Hilzne od 25-240 mm ²		

Za više detalja o izmenjivim matricama pogledajte odeljak : [IZMENJIVE MATRICE](#)