

THK 120 Stona hidraulična glava sa izmenljivim umetcima 10 - 400 mm²



**K13
SERIE**

- Veliki opseg presovanja do 400mm²
- Za povezivanje na hidraulične pumpe sa radnim pritiskom od 700bar
- Povezivanje pomoću brzoskidajućih spojki
- Za montažu za radnu površinu (radni sto)
- BG-usklađena verzija

Odgovarajuće za:

- Izmenljive matrice serije 13, široko presovanje

Tehničke karakteristike		
Sila presovanja	120kN	
Opseg presovanja	10-400mm ²	
Radni pritisak	max. 700bar	
Težina	12kg	
Dimenzije V x Š x D Kataloška	285 x 160 x 110mm	
oznaka	THK120	
Oprema koja se posebno poručuje		
Izmenjive matrice za:		
Cu cevaste kablovske papučice i konektori, std. tip od 16-400mm ²		
Izolovane kablovske papučice konektori, izolovani pin konektori od 10-150mm ²		
Cevaste kablovske papučice i konektori, za fine licnaste provodnike od 10-150mm ²		
Cevaste kablovske papučice i konektori od nerđajućeg čelika (VA) - dvostruko ubodno presovanje od 16-50mm ²		
Cevaste kablovske papučice i konektori od nerđajućeg čelika (VA) - jednostruko ubodno presovanje od 70-95mm ²		
Cevaste kablovske papučice i konektori od nikla - dvostruko ubodno presovanje od 16-50mm ²		
Cevaste kablovske papučice i konektori od nikla - jednostruko ubodno presovanje od 70-95mm ²		
Cu kablovske papučice (DIN 46235) i konektore (DIN 46267, part 1) prema DIN od 10-300 mm ²		
Duple kompresione Cu kablovske papučice 2x50 - 2x120mm ²		
Bezlemni terminali (DIN 46234), konektori i pin terminali (DIN 46230) prema DIN od 16-150mm ²		
Izolovani bezlemni terminali i konektori od 10-95 mm ²		
Oblikovanje spojnica Cu i Al za sektorske kablove od 10 sm - 300 se / 300 sm mm ²		
Al kablovske papučice i konektori po DIN od 10 sm - 300 re / 300se mm ²		
Bim. Al/Cu kablovske papučice i konektori od 10sm - 300re / 300se mm ²		
C kleme od 10-70 mm ²		
H kleme 70-120mm ²		
Hilzne od 25-240 mm ²		

Za više detalja o izmenljivim matricama pogledajte odeljak : [IZMENLJIVE MATRICE](#)