

THK 22 Stona hidraulična glava sa izmenljivim umetcima 6 - 300 mm²



- Veliki opseg presovanja do 300mm²
- Za povezivanje na hidraulične pumpe sa radnim pritiskom od 700bar
- Povezivanje pomoću brzokidajućih spojki
- Za montažu za radnu površinu (radni sto)
- BG-usklađena verzija

Odgovarajuće za:

- Izmenljive matrice serije 22, usko presovanje

Tehničke karakteristike		
Sila presovanja	60kN	
Opseg presovanja	6-300mm ²	
Radni pritisak	max. 700bar	
Težina	8,8kg	
Dimenzije V x Š x D	220 x 160 x 120mm	
Kataloška oznaka	THK22	
Oprema koja se posebno poručuje		
Izmenjive matrice za:		
Cu cevaste kablovske papučice, std. tip od 6-300mm ²		
Izolovane kablovske papučice i spojnice, std. tip, izolovani pin konektori od 10-150mm ²		
Cevaste kablovske papučice i konektori, za fine licnaste provodnike od 10-70mm ²		
Cu cevaste kablovske papučice, pun presek od 1,5 - 16 mm ²		
Cevaste kablovske papučice i konektori od nerđajućeg čelika (VA) - dvostruko ubodno presovanje od 10-50mm ²		
Cevaste kablovske papučice i konektori od nikla - dvostruko ubodno presovanje od 10-50mm ²		
Cu kablovske papučice (DIN 46235) i konektore (DIN 46267, part 1) prema DIN od 6-300 mm ²		
Duple kompresione Cu kablovske papučice 2x70mm ²		
Bezlejni terminali (DIN 46234), konektori i pin terminali (DIN 46230) prema DIN od 10-70mm ²		
Izolovani bezlejni terminali i konektori od 10-70 mm ²		
Oblikovanje spojnica Cu i Al za sektorske kablove od 10 sm - 300 se / 300 sm mm ²		
Al kablovske papučice i konektori po DIN od 10 sm - 300 se / 300sm mm ²		
Bim. Al/Cu kablovske papučice i konektori (Al strana um. A22, Cu strana um. D22) od 10sm - 300se / 300sm mm ²		
C kleme od 10-70 mm ²		
H kleme 70mm ²		
Hilzne od 25-240 mm ²		

Za više detalja o izmenjivim matricama pogledajte odeljak : [IZMENJIVE MATRICE](#)